



Material Safety Data Sheet

GREASEEZE

1. Identification of the material and supplier

PRODUCT NAME:	GREASEEZE
OTHER NAMES	
RECOMMENDED USE	Laundry Pre-spray
COMPANY:	Cleveland Cleaning Supplies Pty Limited ABN: 61 001 175 748
ADDRESS:	23 Forrester Street Kingsgrove NSW 2208 P.O. BOX 320 Kingsgrove NSW 1480 Australia
BUSINESS TELEPHONE:	(02) 9503 0100 1300 760 765 (Australia wide)
BUSINESS HOURS ONLY:	7.30 AM – 5PM (E.S.T.)
FAX:	(02) 9503 0199
EMAIL:	sales@cleveland.com.au
EMERGENCY TELEPHONE:	000
POISONS INFORMATION CENTRE PHONE	13 11 26
FOR EMERGENCY RESPONSE:	000

2. Hazards identification

DANGEROUS GOODS	Classified as HAZARDOUS according to the criteria of NOHSC
RISK PHASES	T TOXIC R10 Flammable R65 Harmful : may cause lung damage if swallowed R66 Repeated exposure may cause skin dryness and cracking. R45 May cause cancer.
SAFETY PHASES	S23 Do not breath fumes/vapour. S24 Avoid contact with skin. S33 Take precautionary measures against static discharges. S43 In case of fire use sand, earth, chemical powder or foam. S45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

3. Composition/ information on ingredients

<u>NAME</u>	<u>CAS</u>	<u>PROPORTION</u>
ALKANES, C9-12-ISO	64742-48-9	>60 %
Other ingredients determined to be non-hazardous according to NOHSC		To 100%

4. First Aid measures

SWALLOWED	Never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. If swallowed DO NOT induce vomiting. For advice contact a Poisons information Centre Phone Australia 13 1126 or a doctor.
EYE	If in eyes, hold eyelids apart and flush eyes continuously with running water. Continue flushing until advised to stop by the poisons Information Centre or a doctor, or for at least 15 minutes. Obtain medical attention immediately.
SKIN	If skin or hair contact occurs, remove contaminated clothing, shoes and leather goods. As quickly as possible, flush contaminated area with lukewarm, gently running water.
INHALED	If symptoms are experienced, such as cough, dry throat, difficulty in breathing, nasal congestion and headaches or dizziness remove source of contamination or move victim to fresh air.
FIRST AID FACILITIES	Ensure eyewash and safety shower facilities are available in workplace.



Material Safety Data Sheet

GREASEEZE

Advice to Doctor Treat symptomatically based on individual reactions of patient and judgement of doctor.

Additional information / Aggravated medical conditions

No Data

5. Fire fighting measures

Suitable extinguishing media

Use carbon dioxide, dry chemical, and foam.
If safe to do so, move undamaged containers from fire area – Do not approach hot containers
Cool containers with water before handling
If impossible to extinguish fire, protect surroundings, withdraw from area and allow fire to burn.

Special protective precautions and equipment for fire fighters

If large amounts are involved wear SCBA and chemical splash suit.

HAZCHEM CODE 3W

6. Accidental release measures

Wear appropriate personal protective equipment and clothing to avoid exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unnecessary personnel. If possible contain the spill. Place inert non-combustible absorbent material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers. Dispose of waste according to federal, Environmental Protection Authority and state regulations. If the spillage enters the waterways contact the Environmental Protection Authority, or your local Waste Management Authority.

7. Handling and storage

PRECAUTIONS FOR SAFE HANDLING

Open containers cautiously as contents may be under pressure. Use only in a well ventilated area. DO NOT store or use in confined spaces. Keep tank covered and containers sealed when not in use. Build up of mists or vapours in the atmosphere must be prevented. Avoid inhalation of vapour and mists, skin or eye contact. Do not use near welding or other ignition sources and avoid sparks. Do not smoke. Wear appropriate protection. It is essential that all who come into contact with this material maintain high standards of personal hygiene i.e. Washing hands prior to eating, drinking, smoking or using toilet facilities.

STORAGE REQUIREMENTS

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, organic peroxides, acids, combustible materials, foodstuffs, and clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Always keep in containers made of the same material as the supply container. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all State and Federal regulations.

8. Exposure controls / Personal protection

NATIONAL EXPOSURE STANDARDS

No exposure standards have been established for this material. Exposure standards recommended by A.S.C.C. Australia for some ingredients are as follows:

	TWA (TIME WEIGHED AVERAGE)	
	mg/m ³	ppm
ALKANES, C9-12-ISO	196ppm (1200mg/m3)	

ENGINEERING CONTROLS Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required.



Material Safety Data Sheet

GREASEEZE

PERSONAL PROTECTION	
RESPIRATOR TYPE	Where ventilation is not adequate, respiratory protection may be required. Respiratory protection should comply with AS/NZS 1715.
EYE PROTECTION	Safety glasses or chemical goggles. Failure to do so may result in eye damage if an accident occurs.
GLOVE TYPE	Chemical resistant gloves provide adequate protection.
CLOTHING	Wear protective plastic or PVC apron to prevent contact with clothing.

Always wash hands before smoking, eating, drinking, or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

9. Physical and chemical properties

APPEARANCE	clear colourless liquid
ODOUR	faint lemon odour
PH	not applicable
VAPOUR PRESSURE	0.231kPa mm Hg (1 atmosphere)
VAPOUR DENSITY	5.0 at 15°C (Air=1)
BOILING POINT	78°C (for liquid concentrate)
BOILINGRANGE	153 -178°C
MELTING POINT	-57.2°C
SOLUBILITY IN WATER	emulsifies
SPECIFIC GRAVITY	0.76 (for liquid concentrate) water = 1.000
FLASH POINT	40°C (Abel closed cup)
FLAMMABILITY LIMITS	lower 0.6% Upper 5.6%

10. Stability and reactivity

Stable under normal conditions of storage and handling. Avoid heat, direct sunlight, open flames or other sources of ignition. Incompatible with oxidizing agents, organic peroxides, acids, combustible materials and sources of ignition. Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide and carbon dioxide. Hazardous polymerization will not occur

11. Toxicological information

Health effects from acute exposure

SWALLOWED	Unlikely to occur during normal use. May cause irritation of the gastrointestinal system. Symptoms may include abdominal pain, nausea, vomiting and diarrhoea. May also cause euphoria, irritability, loss of appetite, sleeplessness, stupor, convulsions, headache dizziness, fatigue, vertigo, loss of consciousness and possible death. Aspiration into lungs may cause pneumonia.
EYE	May be irritating to eyes. On eye contact this product may cause tearing, stinging, blurred vision, and redness.
INHALED	May cause irritation to the respiratory tract and mucous membranes. Inhalation of the vapour may result in headache, nausea and vomiting. High concentrations may cause central nervous system symptoms similar to 'swallowed' above.
SKIN	May cause redness, itching and irritation

Health effects from chronic exposure

Prolonged or repeated contact may cause dermatitis. Long term exposure by swallowing or repeated inhalation may cause degenerative changes in the liver, kidney, gastrointestinal tract and heart muscle.

Toxicology Information

No toxicological information available for this product.

12. Ecological information

Ecotoxicity :	No Data
Persistence and degradability:	This product is expected to biodegrade at a moderate rate and inherently' biodegradable according to OECD Guidelines.



Material Safety Data Sheet

GREASEEZE

Bioaccumulative potential: No acute toxicity to aquatic organisms is expected at the maximum water solubility of this product.

13. Disposal considerations

Disposal: Review federal, state and local government requirements prior to disposal.

14. Transport information

UN CLASS	3295
PROPER SHIPPING NAME	HYDROCARBONS, LIQUID, N.O.S. (ISODECANE AND ISOUNDECANE)
DG CLASS	3
SUBSIDIARY RISK	none allocated
PACKAGING GROUP	III
RECOMMENDED USE	Laundry Pre-spray

15 Regulatory information

POISONS SCHEDULE 5

16. Other information

Produced by: Cleveland Cleaning Supplies Pty Ltd, ABN: 61 001 175 748

Revised : January 2012

Issue: D

DATE OF PREPARATION: 1st January, 2012

© This document is the property of Cleveland Cleaning Supplies Pty Ltd. Alteration is not allowed without written permission of Cleveland Cleaning Supplies Pty Ltd.

Users should verify the currency of this data sheet if more than 5 years old.

The information contained in this material safety data sheet is believed to be accurate on the date of issue and in accordance with the information available to us. Persons dealing with products referred to in this MSDS do so at their own risk. We accept no liability whatsoever for damage or injury however caused arising from use of this information or of suggestions contained herein.

END OF REPORT